



## FEATURES

- All welded construction
- 316L stainless steel wetted parts
- High accuracy
- Pressure up to 5000 PSI (345 bar)

## TYPICAL APPLICATIONS

- Fuel tank level
- Chemical tank level
- Gas compressors
- Chemical processing



## FOR CORROSIVE ENVIRONMENTS

The "X48" Series features all welded stainless steel construction with 316L stainless steel wetted parts. Non-linearity is 0.25% or better with an optional improved non-linearity of better than 0.1%. Standard ranges are from 3 PSI to 5,000 PSI with available outputs of mV/V, 4-20 mA and 0-5 VDC. Also available are optional zero and span adjustments.

## A FULL LINE OF APPROVALS

The "X48" Series has the approvals necessary for use in hazardous areas. Viatran offers a variety of standard options that provides flexibility to meet your specific application needs. Options include alternate pressure ports, electrical connectors and various electrical outputs.

## VIATRAN'S FULL LINE

To complement this series is a full line of pressure measurement products for the process control industry. Our Model 570 and 571 provide mid to high ranges up to 100K PSI and the IDP10 can measure differential pressures as low as 0.5" WC full scale.

## OUR COMMITMENT TO QUALITY

The "X48" series design will perform and maintain on site durability in the most severe applications. To satisfy your unique application requirements, Viatran will also modify our standard products to meet your needs.

Viatran's vision is to be your fastest, easiest and most trusted solution.

Call us today to explore the solutions we have to offer.

**1.800.688.0030**

---

**Your local applications specialist:**

# Models 548 / 748 / 848

## PERFORMANCE

	Full Scale Pressure Range	0-3 thru 0-5000 PSIG, PSIA; 0-15 thru 0-5000 PSIA
		0-15 PSIV*
	Non Linearity	≤±0.25% (optional ≤±0.1% 548/748)
	Hysteresis & Repeatability	±0.05% FSO each
Full Scale Output (FSO)	548	16 mA ±1%
	748	5 Vdc ±1%
	848	mV/V
	Zero Balance	≤±1% FSO
	Long-term Stability	≤±0.25% FSO per 6 months
	Response Time	≤1 milliseconds to reach 90% of FSO
	Temperature Effect on Zero	≤±1% FSO per 100°F (55°C)
	Temperature Effect on Span	≤±1% FSO per 100°F (55°C)
	Compensated Temperature	32°F to 180°F (0°C to 82°C)
Storage Temperature Limits	Operating Temperature	-40°F to 185°F (-40°C to 85°C)
	548 / 748	-40°F to 250°F (-40°C to 121°C)
	848	-65°F to 250°F (-54°C to 121°C)

## ELECTRICAL

Supply Voltage	548 / 748	9.0 to 30 Vdc		
	848	15 Vdc max		
Output Signal	Power Supply Regulation Effect	±0.05% FSO per volt		
	548	4 - 20 mA		
	748	0 - 5 Vdc		
Load Resistance	848	3 to 5 PSI: 5 mV/V. 10 PSI and up: 10 mV/V		
	548	12 Vdc min with 150 ohm and 30 Vdc max with 1050 ohms		
	Circuit Protection	Output may be short-circuited indefinitely. Input polarity may be reversed. Over voltage protected to 1000 volts. <1 msec duration		
	Insulation Resistance	<5nS Conductance		
	Electrical Connection	1/2" NPT (M), 18 AWG wire, 72" long		
		548	748	848
	Red	+Power/Signal	+Power	+Power
	Black	-Power/Signal	+Signal	+Signal
	Green	Case Ground	Case Ground	-Power
	White	N/A	-Power/Signal	-Signal
	Brown	N/A	N/A	Case Ground

## MECHANICAL

Pressure Connection	1/4" - 18 NPT female
Proof Pressure	≤500 PSI lesser of 3x or 1,200 PSI
	>500 PSI lesser of 3x or 9,000 PSI
Burst Pressure	≤500 PSI lesser of 5x or 2400 PSI
	>500 PSI lesser of 5x or 10K PSI
Diameter	1.5 in
Weight	10 oz

## MATERIALS OF CONSTRUCTION

Enclosure Housing	304 and 316 stainless steel
Pressure Connection	316 stainless steel
Sensor	316 stainless steel
Mounting	May be supported by pressure connection
Identification	Laser etched onto body

## ACCESSORIES

- Mounting bracket
- Conduit connection box
- Loop Powered Digital Indicator
- Protective cover

\* For PSIV and Compound Range units:

Temperature Effect on Zero	≤±3.0% per 100°F
Compensated Temperature Range	32°F to 170°F (0°C to 77°C)
Approved units may have an additional .19" housing length for vacuum and compound ranges	
NG and NY hazardous location approval option codes are not available on vacuum and compound range units	
848 output signal	5 mv/V

**CERTIFICATIONS (Consult Factory for Available Options)**

USA	Intrinsic Safety: Class I, II, III, Division 1, Groups A-G; Class I, Zone 0, AEx ia IIC, T4 at Ta<=85°C, T5 at Ta<=40°C Entity, Type 4X Hazardous Locations Explosion Proof: Class I, Division 1, Groups A-D; Class II/III, Division 1, Groups E-G, Class I, Zone 1, AEx d IIC, T5 at Ta<=88°C, NEMA 4X Hazardous Locations Nonincendive: Class I, Division 2, Groups A-D; Class II/III, Division 2, Groups F and G; Class I, Zone 2, Group IIC, T4 at Ta<=80°C, T5 at Ta<=40°C, Type 4X Hazardous Locations		
Canada	Intrinsic Safety: Class I, Division 1, Groups A-D; Class II, Division 1, Groups E-G; Class III; Class I, Zone 0, Ex ia IIC, T4 at Ta<=80°C, T5 at Ta<=40°C Nonincendive: Class I, Division 2, Groups A-D; Class II, Division 2, Groups F-G; Class III, T5 at Ta<=60°C, Type 4		
Europe	EMC Directive 2004/108/EC; EN 61326-1:2006 PED 97/23/EC ATEX Directive 94/9/EC  Intrinsic Safety     ⊕ II 1G, Ex ia IIC T4, Ga -20°C<=Ta <=80°C Flameproof           ⊕ II 2G Ex d IIC T6, Gb -20°C ≤ Ta ≤ 40°C Nonincendive       ⊕ II 3 G Ex nA IIC T4, Gc -20°C =<Ta <=80°C		
Russia	Intrinsic Safety     0Ex ia IIC Ga X   T4: - 2 0°C ≤ Ta ≤ +80°C   T5: - 2 0°C ≤ Ta ≤ +40°C Flameproof           1Ex d IIC Gb X   T6: - 2 0°C ≤ Ta ≤ +40°C Non-Sparking        2Ex nA IIC Gc X   T4: - 2 0°C ≤ Ta ≤ +80°C  Russian Metrology Certificate		

**OPTIONS**

Y().....Alternate pressure ports

DF ..... Bleed port

**PERFORMANCE OPTIONS**

DH.....Special range

DN.....Improved Linearity ≤0.1% FSO (548/748 only)

DM.....Modified output (>0 to 5 Vdc, 748 only)

DQ.....Cleaning for oxygen service

DX .....Modified output (0 to 4.5 Vdc, 748 only)

EA .....Special calibration run

FA .....Russian Metrology Certificate

NG<sup>1</sup>.....ATEX Flameproof label

NH.....Customer specified identification

NJ .....CE design and label

NK .....ATEX Intrinsic Safety label

NX .....CSA Intrinsic Safety label (548/748 only)

NY<sup>1</sup>.....FM Explosion Proof label

NZ .....USA Nonincendive

PW .....1/8 DIN digital indicator

TF.....FM Intrinsic Safety label

TJ.....CSA Division 2 label (548/748 only)

TK.....ATEX Type n label

TW .....EACEx Russia

Note: For units equipped with a breather vent, consideration should be given to ensure that the breather element is kept clear and exposure to contamination is minimized. Applications of some available options may affect standard performance. Consult your Viatran Representative for details.

<sup>1</sup> Not available on PSIV or Compound Range Units.



