

Dynisco PolyClean 26L Fluidized Temperature Bath



PolyClean 26L Fluidized Bath



Sensor Support Tray

Description

The Dynisco PolyClean 26L Fluidized Temperature Bath can be used to clean extrusion tooling and all other types of hardware, shape set medical devices, calibration, testing various sensors and systems, heat treatment of metals as well as heating of reactors, coils, flasks and containers. Fluidized Temperature Baths typically provide faster processing times than ovens and furnaces and are much more thermally stable and uniform. Fast heat up of immersed parts and objects is another major advantage. Fluidized baths are safer to operate than molten salt baths while immersed objects come out clean and dry with no material to remove.

The PolyClean uses a PID temperature controller that has four control zones for improved thermal results. Independent over temperature protection will disable heat if the temperature exceeds 615 °C or in the event of a system failure.

Features

- Fully automate fluidizing air control
- Independent over-temperature protection
- Advanced PID temperature controller for optimum results
- Built rugged for years of reliable operation
- Cleans most tooling in under 60 minutes
- Removes all types of polymer, paint, adhesives and resins
- Large working volume – up to 8.4" diameter by 26" depth in the part basket
- Up to 6500 watts of heat capacity for fast heat up

Performance Characteristics	
Temperature Range	50 to 605 °C
Overall footprint, H x W x D (inches)	41 x 24 x 26
Temperature Stability at 500°C	±1.5 °C
Calibrated Accuracy at 500° C	±10.0 °C
Radial Temperature Uniformity at 500°C	3.0
Heat Up time: Ambient to 600°C	180 minutes
Power Consumption	6.2 Kw (240v, single phase)
Working diameter	9.5 inches
Working depth	28 inches
Working area in basket (diam x depth)	8.4 x 26
Maximum load capacity	52 lbs
Air pressure required	40 PSI
Maximum Air consumption	3.5 SCFM
Total Unit Weight	160 lbs
Operating Weight with Aluminum Oxide	360lbs
Cleaning Capacity	50 lbs
Cool Downtime: Max to 200°C	210 minutes

CE EAC

 **Dynisco**



Azurr-Technology, s.r.o.

Dolní Bečva 579 Tel.: +420 571 647 228
 756 55 Tel.: +420 571 647 310
 Česká republika Email: info@azurr-tech.cz
 www.azurr-tech.cz



Všechny rozměry jsou uvedeny v palcích (mm), pokud není uvedeno jinak. © 2016.
 Společnost Dynisco si vyhrazuje právo provádět změny bez předchozího upozornění.
 Přístupy k dokumentům jako jsou návody k obsluze a jiné podpůrné dokumenty
 naleznete na www.dynisco.com
 Rev.:1216